

PASS-THROUGH WAREWASHER UX-120 ISO

Pass-through glass- and dishwasher. Rack size 500x500mm and door clearance 430 mm.



- √ High load capacity 43 cm: suitable for GN 1/1 and Euronorm
- \checkmark Stainless steel surface filters for greater stability and resistance during intensive use

Premium warewashing

- Soft start: progressive start-up of the washing pump to protect fragile items.
- Colour LCD Display: intuitive communication of the machine status by means of messages, colour codes and icons.
- Dedicated cycles: selection of the ideal washing programme using icons.
- Adaptable: allows the main parameters of the machine to be adjusted to the needs of each user.
- √ TEMPERATURE DISPLAY
- Wash Plus+ function: increases the intensity of the wash cycle for greater cleaning performance
- √ Control panel with IP65 humidity protection.

You will never WASH ALONE

- Tech-Services: our team of technicians will help you so that your machine is always ready for use.
- ✓ Design Services: tell us what your needs are and we will advise you.
- √ 60 years of experience and know-how at your disposal.

INCLUDES

- ✓ Rinse aid pump.✓ 1 glasses basket.
- √ 1 mixed basket (plates).
- √ 1 cutlery basket.

OPTIONAL

- □ Detergent dosing kit.
- □ Drainage pump with level

sensor. Proactive tank water renewal.

Accessories

- □ Tables for pass-through dishwashers
- Manual water softeners
- Automatic water softeners
- □ 500 x 500 mm baskets
- ☐ Inserts & supplements
- □ Central sorting tables
- ☐ Double connection central sorting table
- Prewashing tables for pass-through and rack conveyor dishwashers
- Connecting tables for pass-through dishwashers and rack conveyors
- ☐ Reverse osmosis devices OS-140
- Dosing equipments for AX / UX hood-type dishwashers

SPECIFICATIONS

Basket dimensions: 500 mm x 500 mm Useful height: 430 mm

Cycles: 6

Cycle duration: 60/90/100/150/210" Production baskets / hour: 60/40/36/24/17

Boiler capacity: 12 I Wash tank capacity: 25 I

Consumption and savings

- √ Water consumption/cycle: 2.8 I
- ✓ Automatic saving mode in: 25'
- ✓ Automatic switch-off: 120'

Loading

- ✓ Pump: 1000 W / 1.3 Hp
- √ Tank: 2500 W
- ✓ Boiler: 9000 W



3-stage filtering system.

effectiveness.

- Sani-Control guarantee

 ✓ GUARANTEED DISINFECTION in compliance with standard DIN 10534.
- √ THERMAL LOCK function: Ensures that rinsing will be carried out at the ideal temperature to disinfect the dishes.

New recessed bodywork

- Ergonomic design with rounded corners to prevent the accumulation of dirt and facilitate cleaning.
- Compact tank volume (50% water saving compared to the previous range)

Double-Walled (Ultra ISO)

 Double-Walled Structure: thermo-acoustic insulation to attenuate the sound level and improve energy efficiency

Hydroblade™ washing arms

- Redesigned nozzles for greater washing performance.
- The "monoblock" design delivers durability and resistance to impacts.
- 30% savings in water consumption during rinsing compared to the previous range.

3-stage filter system: surface, tank and extraction

Keeps the washing water in optimal conditions to maintain constant washing performance.

Designed to last

"Flow" opening mechanism: allows the hood to be raised with less effort







PASS-THROUGH WAREWASHER UX-120 ISO

Pass-through glass- and dishwasher. Rack size 500x500mm and door clearance 430 mm.

√ Total loading: 10000 W

External dimensions (W x D x H)

√ Width:650 mm (Wide with handle: 725 mm)

✓ Depth: 756 mm (Bottom with handle: 835 mm)

√ Height: 2000 mm / 1520 mm


Net weight: 116 kg Rinse temperature: 87°C Noise level (1m.): <70 dB(A)

Crated dimensions

760 x 860 x 1530 mm Gross weight: 127 kg

AVAILABLE MODELS

* Ask for special versions availability





www.sammic.co.uk

Food Service Equipment Manufacturer Unit 2, Trevanth Road Troon Industrial Park LE4 9LS - Leicester

uksales@sammic.com Tel.: +44 0116 246 1900



Project	Date
Item	Qty

Approved