



COMBISTEAM GASTRONORM OVEN HX-711

Capacity: 7 trays of GN 1/1.



FOOD PRESERVATION AND SOUS-VIDE
HX COMBISTEAM GASTRONORM OVENS



SALES DESCRIPTION

- ✓ Ideal for restaurants, catering, rotisseries, hotels with kitchens, canteens...
- ✓ Professional combi oven with touchscreen and capacity for 7 trays from our Gastronorm range.
- ✓ Choose between steam, convection, and combi cooking.
- ✓ Program up to 999 recipes with a simple touch.
- ✓ Cook up to 7 dishes at the same time.

Cooking

- ✓ Convection, combi and steam cooking, with fixed timed or with core probe function.
- ✓ Temperature adjustable from 30°C to 280°C.
- ✓ Manual, programmed and/or automatic cooking mode.
- ✓ Manual and / or automatic pre-heating mode settable up to 300°C.
- ✓ HOLD function at the end of manual and / or programmed cooking.
- ✓ Special cycles: Delta T cooking, Time's up for synchronized cooking, Cook & Go for simultaneous cooking, rapid cooking chamber cool-down, regeneration and leavening.
- ✓ Manual humidity supply function.
- ✓ FastSteam technology for immediate steam generation.
- ✓ Tecnología CSSteam para generación de vapor con vaporizador de alta eficiencia.
- ✓ Programmable FCS (Fast Chimney System) technology for the forced extraction of humidity.
- ✓ Automatic SCS (Smart Chimney System) technology for the forced extraction of humidity.
- ✓ Settable ventilation speeds (7) and one pulse speed with automatic inversion of fan rotation.

Recipes

- ✓ Pre uploaded CSRECIPES book divided into categories.
- ✓ MYCOOKBOOK for saving recipes into customizable folders.
- ✓ Possibility to save up to 10 cooking phases per program.

- ✓ Click & Share function for saving recipes with your cover image.

Advanced features on all models

- ✓ 10" multilingual touchscreen display.
- ✓ USB interface for data uploading and downloading (including HACCP data).
- ✓ Integrated WIFI connection configuration.
- ✓ Alarm display with autodiagnosis system.

Structure and consumption

- ✓ 304 stainless steel molded cooking chamber.
- ✓ 304 stainless steel control panel.
- ✓ Oven frontal structure with screwless system.
- ✓ Simply-removable control panel.
- ✓ Simply-approachable right side.
- ✓ Simply-approachable motor compartment.
- ✓ Integrated humidity collector aisle.
- ✓ Multi-point core probe with external link to the cooking chamber.
- ✓ Integrated syphon.
- ✓ Height-adjustable feet.
- ✓ Stackable kit configuration.
- ✓ Tray holder with simply-removable structure.
- ✓ Ergonomic and lightweight handle structure compliant with HACCP standards.
- ✓ Reversible door opening R/L (optional only at the order placement).
- ✓ Double glass door with high thermal insulation and easy inspection with safety fanstop system when the door is open
- ✓ Multi-lamp halogen lighting inside the cooking chamber.

Self-cleaning

- ✓ Integrated retractable shower in option.
- ✓ Automatic oven washing system with monocomponent CSClean (4 + 1 cycles)
- ✓ Detergent loading function.
- ✓ Integrated one-product detergent tank for CSClean (washing).

INCLUDES

- ✓ Multipoint probe.
- ✓ Automatic washing with a single-product detergent tank.
- ✓ Wifi and USB connectivity.



SAMMIC, S.L. · Basarte, 1
20720 AZKOITIA (Gipuzkoa) · SPAIN

product sheet
updated 26/09/2025



COMBISTEAM GASTRONORM OVEN HX-711

Capacity: 7 trays of GN 1/1.



OPTIONAL

- ☐ Left-hand opening option.
- ☐ Voltage 230V 3~
- ☐ Sous-vide probe.
- ☐ Integrated shower.
- ☐ Condensation hood.
- ☐ Tray support for 600 x 400 mm trays.
- ☐ Column composition kit.
- ☐ Stand.

ACCESSORIES

- ☐ Condensation hoods
- ☐ 600 x 400 mm guides for HX-711 / HX-1111
- ☐ Stands for CombiSteam ovens
- ☐ Accessories for stacked installation
- ☐ Probes for CombiSteam ovens
- ☐ HX grill
- ☐ Detergent for CombiSteam ovens
- ☐ 6-egg tray HX
- ☐ Frying tray HX
- ☐ HX chicken grill

SPECIFICATIONS

Capacity
Tray type: GN 1/1
Number of trays: 7
Space between trays: 70 mm
Load capacity: 35 kg
Maximum load per tray: 5 kg

Loading
Total loading: 11000 W
IP Protection grade: IPx4

Distances for installation
Left side: 500 mm

Right side: 50 mm
Back side: 50 mm
Top: 500 mm
Hydraulic connection
Self-cleaning connection: 3/4"
Steam connection (softened water): 3/4"
Feed water pressure (bar): 1.5 - 5 bar
Drain diameter: 32 mm

External dimensions (W x D x H)
External dimensions (W x D x H): 850 x 890 x 890mm
Net weight: 105 kg
Crated dimensions
915 x 1000 x 1045 mm
Volume Packed: 0.95 m³
Gross weight: 123 kg

AVAILABLE MODELS

5120074	HX-711D 380-415/50-60/3N
5120075	HX-711I 380-415/50-60/3N
5120076	HX-711DD 380-415/50-60/3N
5120077	HX-711ID 380-415/50-60/3N
5120083	HX-711D 230/60/3

* Ask for special versions availability

FOOD PRESERVATION AND SOUS-VIDE
HX COMBISTEAM GASTRONORM OVENS

 **sammic** | sammic.com
Food Service Equipment Manufacturer

Polígono Basarte, 1. phone +34 943 15 72 36
20720 Azkoitia, Spain sales@sammic.com



Project	Date
Item	Qty
Approved	

product sheet
updated 26/09/2025