HOOD TYPE DISHWASHER UX-130BCV ISO DD

Rack size 500 mm x 500 mm and door clearance 440 mm. Double-skinned hood.



SALES DESCRIPTION

Top panel.

Sani-Control: guaranteed disinfection.

Double-walled hood: insulation and energy efficiency.

Exclusive Hydroblade™ washing arms: maximum effectiveness.

3-stage filtering system.

Steam condenser: environmental improvement and energy efficiency.

Sani-Control guarantee

- ✓ GUARANTEED DISINFECTION in compliance with standard DIN
- THERMAL LOCK function: Ensures that rinsing will be carried out at the ideal temperature to disinfect the dishes.
- CONSTANT HIGH TEMPERATURE RINSE system for optimal disinfection
- The PRESSURE PUMP guarantees effective high-pressure rinsing.
- √ WRAS certified.

Steam condenser

- Reduces the steam released into the installation by 75%.
- ✓ Factory-integrated condenser module, no installation required.

New recessed bodywork

- Ergonomic design with rounded corners to prevent the accumulation of dirt and facilitate cleaning.
- Compact tank volume (50% water saving compared to the previous range).

Double-Walled (Ultra ISO)

Double-Walled Structure: thermo-acoustic insulation to attenuate the sound level and improve energy efficiency

Hydroblade™ washing arms

- Redesigned nozzles for greater washing performance.
- The "monoblock" design delivers durability and resistance to impacts.

30% savings in water consumption during rinsing compared to the previous range.

3-stage filter system: surface, tank and extraction

√ Keeps the washing water in optimal conditions to maintain constant washing performance.

Designed to last

- ✓ "Flow" opening mechanism: allows the hood to be raised with less effort
- √ High load capacity 43 cm: suitable for GN 1/1 and Euronorm
- Stainless steel surface filters for greater stability and resistance during intensive use

Premium warewashing

- Soft start: progressive start-up of the washing pump to protect
- Top panel: it allows quick and intuitive reading of information, ideal for corner installations.
- Colour LCD Display: intuitive communication of the machine status by means of messages, colour codes and icons.
- ✓ Dedicated cycles: selection of the ideal washing programme using icons.
- √ Adaptable: allows the main parameters of the machine to be adjusted to the needs of each user.
- √ TEMPERATURE DISPLAY
- √ Wash Plus+ function: increases the intensity of the wash cycle for greater cleaning performance
- Control panel with IP65 humidity protection.

You will never WASH ALONE

- ✓ Tech-Services: our team of technicians will help you so that your machine is always ready for use.
- ✓ Design Services: tell us what your needs are and we will advise
- √ 60 years of experience and know-how at your disposal.

INCLUDES

- √ Rinse aid pump.
- ✓ Detergent Dispenser
- √ 1 glasses basket.
- √ 1 mixed basket (plates).
- √ 1 cutlery basket.
- Drainage pump with level sensor. Proactive tank water renewal.



WARE WASHING

updated 01/10/2025 product sheet



HOOD TYPE DISHWASHER UX-130BCV ISO DD

Double-skinned hood.

sammic	Rack size 500 mm x 500 mm and door clearance 440 mm

O	PI	ΓIO	N	ΔL

■ Automatic resin regeneration water softener with salt detector.

Accessories

- ☐ Tables for pass-through dishwashers
- Manual water softeners
- □ Automatic water softeners
- □ 500 x 500 mm baskets
- ☐ Inserts & supplements □ Central sorting tables
- Double connection central sorting table

- Prewashing tables for pass-through and rack conveyor dishwashers
- Connecting tables for pass-through dishwashers and rack conveyors
- ☐ Reverse osmosis devices OS-140

SPECIFICATIONS

Crated dimensions 760 x 860 x 1500 mm Gross weight: 154 kg

AVAILABLE MODELS

1303437 UX-130SBCV 400/50/3N DD

* Ask for special versions availability

🗲 sammic | sammic.asia **Food Service Equiment Manufacturer**

asia@sammic.com phone: +65 67480511 3018 Ubi Road 1 408710 SINGAPORE

vietnam@sammic.com phone: +84 (0) 862493814

thailand@sammic.com phone: +66 (0) 993425561



Project	Date
Item	Qty
Approved	